



AL-KO
QUALITY FOR LIFE

HIGH-PERFORMANCE INDUSTRIAL VACUUM CLEANER

AL-KO JET STREAM M

MORE THAN CLEAN AIR



MADE IN GERMANY

WET/DRY VACUUM CLEANER WITH AUTOMATIC FILTER CLEANING

AL-KO JET STREAM M

Powerful and robust high capacity wet/dry vacuum cleaner, approved for class M dusts and designed for use in environments with medium hazardous dusts such as hardwood, stucco, varnish or concrete. The AL-KO JET STREAM M is compact, handy and ideal for work on construction sites. The innovative cleaning system automatically cleans the main filter by reversing the air flow, ensuring constant suction and considerably reducing machine downtime, allowing the operator to work without interruption with high suction power. Equipped with a power socket for electric tools (max. 2400 W) and the COMBI kit for the connection of pneumatic tools (optional), to guarantee an operating pressure of up to 10 bar. The device can be switched on manually or automatically (controlled by the connected tool). In addition, the vacuum cleaner can be started directly from the hose with the optional remote control kit. The AL-KO JET STREAM M is available with antistatic accessories as standard, to protect against any electrostatic charges that may occur during work.

The **JET STREAM M** is designed to meet the requirements of craft and industry. The wet/dry vacuum cleaner with automatic filter cleaning ensures continuity and maximum safety at work.



Accessory hook and cable holder, robust and visible cable



Possibility to choose different diameters for the accessories



Connecting power tools



Cleaning of the filter



PTFE flat filter



Suction tube storage



Kit COMBI (as an option)



Antistatic accessories

PRODUCT IDENTIFICATION

Model	Art. no.
JET STREAM M	192 684

TECHNICAL DATA

Motor performance	220-240 V / 50/60 Hz
Maximum power reception	1,350 W
Power rating	1,100 W
Maximum power of socket of the appliance	2,400 W
Filter type	Flat filter PTFE (class M)
Filter area (flat filter)	500 cm ²
Filter cleaning system	Automatic
Max. volume flow	273 m ³ /h
Max. vacuum	25,000 Pa
Tank capacity	41 L
Effective capacity	26 L
Fleece filter bag capacity	20 L
IP-Code	IPX4
Filter class	M
Diameter of the accessories	21-29-33-36-38 mm
Cable length	7 m
Weight (without accessories)	21 kg
Dimensions	625 x 385 x 545 mm

STANDARD ACCESSORIES

Model	Art. no.
Flexible and antistatic hose Ø 33-4 m	192 695
Chrome extension tube 0.5 m (2 pcs.)	192 696
Antistatic nozzle for dry floors P340 Ø 36	192 697
Universal adapter Ø 36	192 698
Antistatic seal nozzle Ø 36	192 699
Closing cap Connecting sleeve	192 851
Flat filter PTFE (class M)	192 694
Fleece filter bag L 20	---

OPTIONAL ACCESSORIES

Model	Art. no.
Flexible and antistatic hose Ø 29-4 m	192 685
Flexible and antistatic hose Ø 38 - 4 m	192 686
Water nozzles V340 Ø 36	192 687
Kit COMBI	192 688
Remote Control Kit	192 689
Toolbox adapter	192 690
Transport handle	192 691
PE bag	192 692
Fleece filter bag L 20 (10 St.)	192 693



Max Ø (mm)	Flow min (m ³ /h)
21	26
29	48
33	62
36	73
38	100